

ENERVEX® HMM HEAT-MODULE MANIFOLD

009.4170.1118 02.20

Product Information

Use

The HMM heat-module manifolds are used in conjunction with the VHX Economizers. They are used to connect the heating on the supply and return sides.

Description

The manifolds are designed to accept the 1-1/4" NPT flexible hoses used with the VHX heat modules. The connection flange is an ANSI 300# RFSW. In addition the manifold has two ports with 1/2" NPT threads and has a 1" NPT plugged connection for a pressure relief valve (not included).

Material

The manifold and all fitting are made of 304 stainless steel.

Warranty

2-Year Factory Warranty. Complete warranty conditions are available from ENERVEX Inc.

Dimensions

Product No.	HMM-2	HMM-3	HMM-4	HMM-5	HMM-6	HMM-7	HMM-8	
	417.0010.0201	417.0010.0301	417.0010.0401	417.0010.0501	417.0010.0601	417.0010.0701	417.0010.0801	
Connections	2	3	4	5	6	7	8	
A	in/mm	31.06 / 789	41.81 / 1062	52.86 / 1343	64.06 / 1627	75.21 / 1910	86.91 / 2208	97.91 / 2487
B	in/mm	1/2" NPT						
C	in/mm	16.24 / 413	16.24 / 413	16.24 / 413	16.24 / 413	16.24 / 413	16.24 / 413	16.24 / 413
D	in/mm	11.1 / 282	11.1 / 282	11.1 / 282	11.1 / 282	11.1 / 282	11.1 / 282	11.1 / 282
E	in/mm	1-1/4" NPT						
F	in/mm	7.06 / 179	7.06 / 179	7.06 / 179	7.06 / 179	7.06 / 179	7.06 / 179	7.06 / 179
G	in/mm	1" NPT						
H	in/mm	9.06 / 230	9.06 / 230	9.06 / 230	9.06 / 230	9.06 / 230	9.06 / 230	9.06 / 230
J	in/mm	7.5 / 191	7.5 / 191	7.5 / 191	8.3 / 210	8.3 / 210	10.0 / 254	1.0 / 254
Pipe Size	2-1/2" Sch. 40			3" Sch. 40		4" Sch. 40		

