



Fan		EDrive				Motor	
Model	Voltage (V)	Item #	Input Voltage (V)	Output Voltage (V)	Max Input Current (A)	Not Field Adjustable	Field Adjustable
BEF 225x	3x208-240	321.2206.1200	1x120	3x200-240	7.8	200V	-
	3x208-240	321.2206.2200	3x200-240	3x200-240	3.4	200V	-
	3x380-480	321.2206.4200	3x380-480	3x380-480	3.5	400V	-
BEF 315x	3x208-240	321.2208.1200	1x120	3x200-240	15.8	200V	-
	3x208-240	321.2208.2200	3x200-240	3x200-240	5.6	200V	-
	3x380-480	321.2208.4200	3x380-480	3x380-480	3.5	400V	-
BEF 355x	3x208-240	321.2210.1200	1x120	3x200-240	15.8	200V	-
	3x208-240	321.2210.2200	3x200-240	3x200-240	5.6	200V	-
	3x380-480	321.2210.4200	3x380-480	3x380-480	3.5	400V	-
BEF 450x	3x208-240	321.2212.2200	3x200-240	3x200-240	8.9	-	200V (DELTA)
	3x380-480	321.2212.4200	3x380-480	3x380-480	5.6	-	400V (WYE)
BEF 500x	3x208-240	321.2214.2200	3x200-240	3x200-240	26.4	200V	-
	3x380-480	321.2214.4200	3x380-480	3x380-480	17.2	400V	-
BEF 560x	3x208-240	321.2216.2200	3x200-240	3x200-240	26.4	200V	-
	3x380-480	321.2216.4200	3x380-480	3x380-480	17.2	400V	-
BEF 630x	3x208-240	321.2218.2200	3x200-240	3x200-240	33.3	200V	-
	3x380-480	321.2218.4200	3x380-480	3x380-480	21.2	400V	-
BEF 710x	3x380-480	321.2220.4200	3x380-480	3x380-480	34.2	400V	-
BEF 800x	3x380-480	321.2222.4200	3x380-480	3x380-480	51.9	400V	-

Note:

The wire sizes shown are typical and may not apply to all jobs. This system must be installed in compliance with the NFPA 70 National Electric Code and/or any local codes.

— Line Voltage

----- Low Voltage Signal

PROPRIETARY AND
CONFIDENTIAL

The information contained in this drawing is the sole property of ENERVEX, Inc. Any reproduction in part or as a whole without the express written consent of ENERVEX, Inc. is prohibited.

NOT TO SCALE

ENERVEX®
GREEN BEFORE GREEN WAS IN

1685 Bluegrass Lakes Pkwy
Alpharetta, GA 30004
(770)587-3238
Fax (770)587-4731

TITLE	CONNECTION DIAGRAM	DATE	2/2/2024
NAME	EXHAUST ONLY - MEC 24 & BEFX	JOB #	GENERIC
DWG BY	AS	SHEET	1 OF 2
		REV	# 1