



Fan		EDrive				Motor	
Model	Voltage (V)	Item #	Input Voltage (V)	Output Voltage (V)	Max Input Current (A)	Not Field Adjustable	Field Adjustable
EFV 400	3x208-240	321.2310.2200	3x200-240	3x200-240	5.6	-	200V (DELTA)
	3x380-420	321.2310.4200	3x380-480	3x380-480	3.5	-	400V (WYE)
EFV 450	3x208-240	321.2312.2200	3x200-240	3x200-240	8.9	-	200V (DELTA)
	3x380-420	321.2312.4200	3x380-480	3x380-480	5.6	-	400V (WYE)

Note:

The wire sizes shown are typical and may not apply to all jobs. This system must be installed in compliance with the NFPA 70 National Electric Code and/or any local codes.

— Line Voltage - - - - Low Voltage Signal

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of ENERVEX, Inc. Any reproduction in part or as a whole with out the express written consent of ENERVEX, Inc. is prohibited.

NOT TO SCALE

ENERVEX
GREEN BEFORE GREEN WAS IN

1685 Bluegrass Lakes Pkwy
Alpharetta, GA 30004
(770)587-3238
Fax (770)587-4731

TITLE	CONNECTION DIAGRAM	DATE	2/2/2024
NAME	EXHAUST ONLY - MEC 24 & EFV 400-450	JOB #	Generic
DWG BY	AS	SHEET	1 OF 2
		REV	# 1